



T62 Graphite Sheet

REACH Compliant

Features

- · Ultra high thermal conductivity
- Easy to assemble
- · Low mass and space saving
- · EMI reduction

Application:

Suitable for products requiring flat temperature

Electronic Components - 5G, Aerospace, AI, AIoT, AR/VR/MR/XR, Automotive, Consumer Devices, Datacom, Electric Vehicle, Electronic Products, Energy Storage, Industrial, Lighting Equipment, Medical, Military, Netcom, Panel, Power Electronics, Robot, Servers, Smart Home, Telecom, etc.

Properties

Properties	Unit	T62	T62-1	T62-2	Tolerance	Test Method
Thermal Conductivity (XY axis)	W/m•K		400		-	AC Calorimeter
Thermal Conductivity (Z axis)	W/m•K	20	15	5	±10%	Laser Flash
Thickness	mm	0.13	0.16	0.2	±0.03	Micrometer
	inch	0.0051	0.0063	0.0079	-	-
Color	-	Black			-	-
Structure	-	Graphite	Graphite Adhesive	PET Graphite Adhesive	-	-
Density	g/cm³	1.5	1.5 1.5~1.8		±5%	ASTM D792
Graphite Contained	%	>98			-	-
Operating Temperature	° C	-40~+400 -30~+100		-	-	

^{*}Die-cut for different shapes

No.33, Ln.50, Daren Rd., Taoyuan Dist., Taoyuan City 330058, Taiwan **E** service@tglobalcorp.com T +886-3-361-8899 W www.tglobalcorp.com









[※]Available to apply adhesive

[%] For other thickness, please contact product consultant.