

Vapor Chamber

Features

- Two-dimensional heat transfer
- Passive component
- High stability
- 10 times efficiency higher than heat pipe


Applications

Best for high performance applications

Electronic components - 5G, Aerospace, AI, AIoT, AR/VR/MR/XR, Automotive, Consumer Devices, Datacom, Electric Vehicle, Electronic Products, Energy Storage, Industrial, Lighting Equipment, Medical, Military, Netcom, Panel, Power Electronics, Robot, Servers, Smart Home, Telecom, etc.

Mechanism

Vapor chamber is two-dimensional thermal conduction. Therefore, it is a more efficient heat dissipation way for solve higher level thermal problem. The inside of vapor chamber is a capillary structure vacuum chamber. After the working fluid absorbs the heat, it will vaporize rapidly and flow to cooling zone. When it exchanged heat with the external, it will condense back to fluid and flow back to heat zone. This is the circulation of vapor chamber.



Project process



Step 1 | RFQ

Submission of technical requirement through T-Global Website



Step 2 | Specification

Configuration of heat allocation, source area and power



Step 3 | Proposal

System analysis with solution



Step 4 | Kick off

Milestones per production plan

Design Guide

※ Heat Size 30X30 mm

Size (mm) \ Q-Max	Thickness (mm)		
	2.0	3.0	4.0
60X80	50	70	90
90X90	80	120	160
100X100	140	200	260
120X80	130	200	250
180X150	160	250	300
200X120	200	300	400
350X100	220	350	450

Different industries will require different specifications, please contact us directly for the most suitable specifications.

T-Global Technonology Co., Ltd.

No.33, Ln.50, Daren Rd., Taoyuan Dist., Taoyuan City 330058, Taiwan

T +886-3-361-8899 E service@tglobalcorp.com W www.tglobalcorp.com

Version20
20250219



NOTICE: The information contained herein is to the best of our knowledge true and accurate. Values stated in this technical data sheet represent typical values as not all tests are run on each lot of material produced. All specifications are subject to change without notice. The protective film and release paper do not affect the function of the product. If there is no special requirement, the default depends on T-Global. Since the varied conditions of potential use are beyond our control, all recommendations or suggestions are presented with out guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology's invoice, quotation, or order acknowledgment. We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to manufacture or to use any product in conflict with existing or future patents covering any product or material or its use.